

**PURPOSE**

To confirm that the X Locks have been set in the appropriate landing nipple.

**ASSEMBLY PARTS**

1. Fishneck
2. Core
3. Body

**OPERATION**

Install desired shear pin and attach to tool string, lower into wellbore. Set down on top of lock mandrel and jar down, remove toolstring from wellbore and inspect the X Check Set Tool. If the pin is sheared in the X Check Set, this will indicate that the lock mandrel is set correctly, if it is not sheared, this will indicate that the fishneck of the lock mandrel is not all the way down into the set position and should be dealt with accordingly.

Nominal Size		1.50"	2.00"	2.50"
Assembly Number		0202XCS150A0	0202XCS200A0	0202XCS250A0
Item	Part Name			
1	Fishneck	0202XCS15001	0202XCS20001	0202XCS25001
2	Core	0202XCS15002	0202XCS20002	0202XCS25002
3	Body	0202XCS15003	0202XCS20003	0202XCS25003
Top Thread Connection		0.938" - 10 UN	0.938" - 10 UN	0.938" - 10 UN
Max O.D.		1.42"	1.75"	2.16"
Fishneck size		1.18"	1.375"	1.375"

Nominal Size		3.00"	4.00"
Assembly Number		0202XCS300A0	0202XCS400A0
Item	Part Name		
1	Fishneck	0202XCS30001	0202XCS40001
2	Core	0202XCS30002	0202XCS40002
3	Body	0202XCS30003	0202XCS40003
Top Thread Connection		1.062" - 10 UN	1.062" - 10 UN
Max O.D.		2.687"	3.48"
Fishneck size		1.75"	2.31"

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061