



PURPOSE

The Halliburton style CRN Profile Nipple is a non-selective type nipple that is placed at the bottom of the tubing string. The CRN is a non-selective type profile nipple which means it cannot be ran in conjunction with other CRN nipples of the same size, as the plugging equipment cannot pass through the no-go or restriction in the bottom of the nipple.

The CRN Profile Nipple typically comes with EUE box x pin thread connections, but is not limited to this; special or premium connections are available upon request as well as a wide range of materials for adverse well conditions.

The CRN Profile Nipple is typically used in situations where pressure may exceed the limits of the X line equipment, or in conditions where size restriction require specific profile diameters.

Halliburton Style CRN							
Tubing O.D.		Seal Bore		No-Go I.D.		Min O.D.	
IN	MM	IN	MM	IN	MM	IN	MM
2.375"	60.33	1.71"	43.43	1.56"	39.62	2.560"	65.02
2.375"	60.33	1.78"	45.24	1.64"	41.66	2.560"	65.02
2.375"	60.33	1.875"	47.03	1.683"	43.59	2.560"	65.02
2.875"	73.02	2.125"	53.98	1.937"	49.20	3.109"	78.97
2.875"	73.02	2.188"	55.58	2.010"	51.05	3.109"	78.97
2.875"	73.02	2.31"	58.75	2.078"	54.13	3.109"	78.97
3.500"	88.90	2.56"	65.07	2.329"	59.16	3.687"	93.65
3.500"	88.90	2.75"	69.85	2.62"	66.5	3.687"	93.65
4.500"	114.30	3.437"	87.30	3.162"	82.80	5.200"	132.08
4.500"	114.30	3.68"	93.68	3.456"	87.78	5.200"	132.08
4.500"	114.30	3.81"	96.85	3.725"	94.62	5.200"	132.08

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061