



**PURPOSE**

The Junk Catcher is used to reduce buildup of debris on top of sub surface tools.

**ASSEMBLY PARTS**

1. Fishneck
2. End Cap

**OPERATION**

Tighten end cap onto fishneck and attach to GS Running / Pulling tool and hoist inside of lubricator. Lower into wellbore to top of sub surface tool, jar down to shear GS. Remove tool string from wellbore.

**PRECAUTIONS**

If a large amount of debris is expected, an extension barrel may be added to accommodate added volume. Ensure that jarring down to release the junk catcher will not damage equipment below.

**\* Inquire about custom sizes and extension barrels. \***

| Nominal Size    |           | 1.50"        | 2.00"        |
|-----------------|-----------|--------------|--------------|
| Assembly Number |           | 0601JCX150A0 | 0601JCX200A0 |
| Item            | Part Name |              |              |
| 1               | Fishneck  | 0601JCX15001 | 0601JCX20001 |
| 2               | End Cap   | 0601JCX15004 | 0601JCX20004 |
| Max O.D.        |           | 1.465"       | 1.843"       |
| Fishneck size   |           | 1.075"       | 1.375"       |

| Nominal Size    |           | 2.50"        | 3.00"        |
|-----------------|-----------|--------------|--------------|
| Assembly Number |           | 0601JCX250A0 | 0601JCX300A0 |
| Item            | Part Name |              |              |
| 1               | Fishneck  | 0601JCX25001 | 0601JCX30001 |
| 2               | End Cap   | 0601JCX25004 | 0601JCX30004 |
| Max O.D.        |           | 2.25"        | 2.73"        |
| Fishneck size   |           | 1.81"        | 2.31"        |

| Nominal Size    |           | 4.00"        | 4.50"        |
|-----------------|-----------|--------------|--------------|
| Assembly Number |           | 0601JCX370A0 | 0601JCX450A0 |
| Item            | Part Name |              |              |
| 1               | Fishneck  | 0601JCX37501 | 0601JCX45001 |
| 2               | End Cap   | 0601JCX40002 | 0601JCX45002 |
| Max O.D.        |           | 3.75"        | 4.50"        |
| Fishneck size   |           | 3.125"       | 3.125"       |