



PURPOSE

The Shock Absorber is used to limit the shock transmitted to the recorders during setting and pulling operations that require jarring impacts.

ASSEMBLY PARTS

1. Fishneck
2. Barrel
3. Top Spring
4. Shaft
5. Bottom Spring
6. Shaft Bushing
7. Bottom Sub

The housing contains the springs and the plunger.

The springs are located one above the plunger and one spring below on the plunger shaft.

Nominal Size		1.25"	1.50"	1.62"
Assembly Number		1201SA125A0	1201SA150A0	1201SA168A0
Item	Part Name			
1	Fishneck *	1201SA12501	1201SA15001	1201SA16801
2	Barrel	1201SA12502	1201SA15002	1201SA16802
3	Top Spring	1201SA12503	1201SA15003	1201SA15003
4	Shaft	1201SA12504	1201SA15004	1201SA15004
5	Bottom Spring	1201SA12505	1201SA15005	1201SA15005
6	Shaft Bushing	1201SA12506	1201SA15006	1201SA16806
7	Bottom Sub *	1201SA12507	1201SA15007	1201SA16807
Top Thread Connection		0.938"-10 UNC	0.938"-10 UNC	0.938"-10 UNC
Lower Thread Connection		0.938"-10 UNC	0.938"-10 UNC	0.938"-10 UNC
Fishneck size		1.18"	1.18"	1.18"

* Available with 0.75" UNF thread connections on request.