



PURPOSE

To locate and retrieve wireline from the wellbore.

ASSEMBLY PARTS

1. Fishneck
2. Mandrel
3. Top Sub
4. Body
5. Washer
6. Dart
7. Tapered Sleeve
8. Skirt

OPERATION

Attach to the tool string and lower into wellbore until the top of the wire is found. Work the Wire Retriever up and down until trapping the wire between the skirt and the tapered cone. Once this has been achieved, remove the tool string and broken wire from the wellbore.

APPLICATIONS

The Wire Retriever may be used when there is a desire to locate or retrieve a broken (parted) slickline or wire from the wellbore. Different size fingered skirts are available for various tubing size.

*** Specify skirt O.D.when ordering ***

Nominal Size		2.00"
Assembly Number		0506WG200A0
Item	Part Name	
1	Fishneck	0506WG20001
2	Mandrel	0506WG20002
3	Top Sub	0506WG20003
4	Body	0506WG20004
5	Washer	0506WG20005
6	Dart	0506WG20006
7	Taper Sleeve	0506WG20007
8	Skirt – 1.86"	0506WG18608
9	Skirt – 2.25"	0506WG22808
10	Skirt – 2.70"	0506WG27008
Top Thread Connection		0.938"10 UN
Max O.D.		"Skirt O.D."
Fishneck size		1.37"