



#### PURPOSE

To achieve communication between the annulus (casing) and the tubing columns, with the ability to segregate the same communication.

#### ASSEMBLY PARTS

1. Upper Sub
2. Inner Sleeve
3. Ported Connector
4. Inner Closing Sleeve
5. Bottom Sub
6. V-Packing
7. Male Backup Ring
8. Female Backup Ring
9. Split Segments
10. O-Rings

#### DESCRIPTION

Two versions of sliding sleeves are available:

- a. Shift up to open version.
- b. Shift down to open version.

The most common of the two is shifting up to open.

All sliding sleeves manufactured by E. Brace Tool require a Halliburton style B positioning tool to shift open or closed.

Sliding sleeves are run in the tubing string as part of the tubing completion, and are available with Baker style, as well as Halliburton style profiles in a wide array of materials, sizes and thread specifications.

More information available upon request.

Type CFU and CFD					
Tubing O.D.		Profile Bore (X)		Tool O.D.	
IN	MM	IN	MM	IN	MM
2.375"	60.33	1.78	45.24	3.125"	79.37
3.375"	60.33	1.81"	46.02	3.125"	79.37
2.375"	60.33	1.875"	47.63	3.125"	79.37
2.875"	73	2.25"	57.15	3.745"	95.12
2.875"	73	2.313"	58.75	3.745"	95.12
3.500"	88.90	2.750"	69.85	4.50"	101.72
3.500"	88.90	2.813"	71.45	4.50"	101.72

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061