



#### PURPOSE

The quick connect is used to connect two wireline components without the use of wrenches. The tool proves essential in wireline industry as it enhances performance. It reduces making and breaking of thread connections on the tool string thus adds safety.

#### ASSEMBLY PARTS

1. QC pin to threaded box
2. Spring
3. Lock Plate
4. Threaded Pin to QC Box

#### OPERATION

The crossover with the threaded pin should be attached to the tool string, the crossover with the threaded box should be attached to the desired tool.

To join the Quick Connect, insert the Quick Connect pin into the Quick Connect box, compress the spring and turn 90 degrees to the right or left to lock into place.

#### QUICK CONNECT PIN TO THREADED BOX

Nominal Size		1.50"	1.75"
Item	Thread Size		
1	0.938 - 10 UN	0101COQ15002	0101COQ17503
2	1.062 - 10 UN	0101COQ15008	0101COQ17502
Top Thread Connection		QC PIN	1.75 QC PIN
Max O.D.		1.50"	1.75"
Fishneck size		1.375"	1.75"

#### THREADED PIN TO QUICK CONNECT BOX

Nominal Size		1.50"	1.75"
Item	Thread Size		
1	0.938 - 10 UN	0101COQ150A0	0101COQ175A0
2	1.062 - 10 UN	0101COQ150A1	0101COQ175A1
Max O.D.		1.50"	1.75"
Fishneck size		1.375"	1.75"

\*Quick Connects are available on other tools upon request

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061